Crafted Connections Collection

Bound To Last
Dual Effect
Thread Lightly

Interface®

Crafted Connections™ Collection

Dial in neutral. Or dial it up.

The loom. The shuttle. The weft and warp. Patient hands shaping threads into something timeless.

Crafted Connections honours the traditions of textile art—changing the way you look at neutrals and subtle accenting.

Thread Lightly™ captures weaving's sophistication. Bound to Last™ brings mid-century soul to bouclé's curled textures. Dual Effect™ unites batik style with geometric patterning for modern floors.

Designs that bring warmth, character, and a sense of the human touch—whether used on their own, or in artful combination.

PRODUCT THREAD LIGHTLY **COLOUR** ONYX/TAN
PRODUCT BOUND TO LAST **COLOUR** ONYX **INSTALLED** MONOLITHIC

PRODUCTS DUAL EFFECT & THREAD LIGHTLY **COLOUR** LINEN **INSTALLED** BRICK

PRODUCT DUAL EFFECT **COLOUR** OAT
PRODUCT THREAD LIGHTLY **COLOUR** OAT/MOSS **INSTALLED** MONOLITHIC

PRODUCT DUAL EFFECT **COLOUR** FOSSIL **INSTALLED** MONOLITHIC
PRODUCT E616 **COLOUR** JUTE **INSTALLED** ASHLAR

Bound To Last Colour Range

1921001 ASH

1921002 FOSSIL

1921003 OAT

1921004 JETTY

1921005 MICA

1921006 ONYX

1921007 NAVY

1921008 FLANNEL

1921009 LINEN

Specifications

Style Code	1921
Product Construction	Tufted Patterned Textured Loop Tile
Yarn System	100% Recycled Solution Dyed Nylon
Machine Gauge	1/10
Pile Thickness	3.5mm (± 0.5mm) *(Asia)* | 3.4mm (± 0.5mm) *(Australia & New Zealand)*
Total Thickness	6.9mm (± 0.5mm) *(Asia)* | 6.7mm (± 0.5mm) *(Australia & New Zealand)*
Tile Size	50 x 50 cm
Carbon Footprint	6.31kg CO_2 *(Asia)* | 5.78kg CO_2 (± 0.5mm) *(Australia & New Zealand)*
Area of Use	Commercial Heavy Use
ACCS Grading *(Australia & New Zealand Only)*	Commercial Extra Heavy Duty & Stairs
Lifetime Antimicrobial	Intersept®
Soil / Stain Protection	Protekt2®

View the full product specification on interface.com

Installation Methods

ASHLAR

BRICK

MONOLITHIC

QUARTER-TURN

PRODUCT BOUND TO LAST **COLOUR** NAVY **INSTALLED** MONOLITHIC

PRODUCT DUAL EFFECT **COLOUR** MICA **INSTALLED** MONOLITHIC

Dual Effect Colour Range

1922001 ASH

1922002 FOSSIL

1922003 OAT

1922004 JETTY

1922005 MICA

1922006 ONYX

1922007 NAVY


1922008 FLANNEL

1922009 LINEN

Specifications

Style Code	1922
Product Construction	Tufted Patterned Textured Loop Tile
Yarn System	100% Recycled Solution Dyed Nylon
Machine Gauge	1/10
Pile Thickness	3.5mm (± 0.5mm) *(Asia)* | 3.2mm (± 0.5mm) *(Australia & New Zealand)*
Total Thickness	6.7mm (± 0.5mm) *(Asia)* | 6.4mm (± 0.5mm) *(Australia & New Zealand)*
Tile Size	50 x 50 cm
Carbon Footprint	6.18kg CO_2 *(Asia)* | 5.70kg CO_2 (± 0.5mm) *(Australia & New Zealand)*
Area of Use	Commercial Heavy Use
ACCS Grading *(Australia & New Zealand Only)*	Commercial Extra Heavy Duty & Stairs
Lifetime Antimicrobial	Intersept®
Soil / Stain Protection	Protekt2®

View the full product specification on interface.com

Installation Methods

ASHLAR

BRICK

MONOLITHIC

QUARTER-TURN

Thread Lightly Colour Range

1920001 ASH

1920002 FOSSIL

1920003 OAT

1920004 JETTY

1920005 MICA

1920006 ONYX

1920007 NAVY

1920008 FLANNEL

1920009 LINEN

1920010 ASH/SAGE

1920011 FOSSIL/TEAL

1920012 OAT/MOSS

1920013 JETTY/RUST

1920014 MICA/OCEAN

1920015 ONYX/TAN

1920016 NAVY/PINE

1920017 FLANNEL/OLIVE

1920018 LINEN/LILAC

Specifications

Style Code	1920
Product Construction	Tufted Patterned Textured Loop Tile
Yarn System	100% Recycled Solution Dyed Nylon
Machine Gauge	1/10
Pile Thickness	2.8mm (± 0.5mm) *(Asia)* | 2.7mm (± 0.5mm) *(Australia & New Zealand)*
Total Thickness	6.3mm (± 0.5mm) *(Asia)* | 6.0mm (± 0.5mm) *(Australia & New Zealand)*
Tile Size	50 x 50 cm
Carbon Footprint	6.05kg CO_2 *(Asia)* | 5.62kg CO_2 (± 0.5mm) *(Australia & New Zealand)*
Area of Use	Commercial Heavy Use
ACCS Grading *(Australia & New Zealand Only)*	Commercial Extra Heavy Duty & Stairs
Lifetime Antimicrobial	Intersept®
Soil / Stain Protection	Protekt2®

View the full product specification on interface.com

Installation Methods

ASHLAR

BRICK

MONOLITHIC

QUARTER-TURN

Why Our Modular Flooring?

Modular Flooring
Performance and flexibility. Interface's standard backing systems set the industry standard for modular performance. Tiles stay on the floor with no upcurl, no tapping and no rippling effect, yet are easy to selectively replace. Our modular carpet is easier to handle than bulky roll carpet and produces an average of just 2-5% waste compared to roll carpet's average of 15% . And it installs seamlessly with our LVT, no transition strips needed.

ReEntry
At Interface, an *end of life solution* of our products is a reality. ReEntry is our innovative programme to reclaim materials used in our product. Taking back our product at end of life is a service we provide our customers to ensure that none of the products they use will end up in landfill. Whether it is recycling into new product or re-purposing, we see our customer's waste as an opportunity for new product life.

TacTiles®
No glue installation. Our revolutionary TacTiles installation system eliminates the need for glue, adhering tiles securely together to form a floor that "floats" for greater flexibility, easier replacement and long-term performance. The result? Less mess, less waste and virtually no VOCs, not to mention an environmental footprint that is over 90% lower than that of traditional glue adhesives.

Intersept®
Mold protection. Our proprietary preservative, Intersept, protects our modular carpet against mould growth and odour-causing bacteria—guaranteed. Intersept treated carpet, with proper maintenance, shows no mould or bacterial growth when tested as per the ASTM E2471 Standard Test Method. Intersept is EPA-approved for safe use in carpet, water insoluble and contains no halogens, heavy metals, phenols or formaldehyde.

Protekt²®
Stain protection. The life and performance of your flooring is extended with Protekt², our patented stain resistant protection. Protekt² uses advanced technology to provide a lasting barrier against permanent soiling and staining, which simplifies the cleaning process and enhances the longevity of your carpet. Protekt² is product specific, please refer to individual product specifications for details.

Health Product Declaration (HPD) –
A transparency tool for evaluating whether a product supports Green Chemistry. As part of our work on Health and Materials, Interface continuously reduces the environmental and health impacts of our products through elimination of materials of concern.

15-Year Warranty
Interface products are warranted for 15 years against excessive surface wear, edge ravel, backing separation, shrinking, stretching and static electricty even under castor chair conditions.

Local Manufacturing
We combine local responsiveness with a global experience. Being part of the same communities as our customers, we foster collaborative, committed, and productive relationships. Our carpet tiles are manufactured in Australia and China, contributing to local economies and the environment.

All Interface manufacturing facilities in the Asia Pacific region maintain registration to ISO 9001 Quality Management Systems and ISO 14001 Environmental Management Systems.

Third Party Certifications

Environmental Product Declaration (EPD)
The Environmental Product Declaration (EPD) is a third party verified environmental certification classified as Type III that quantifies and verifies the lifecycle impacts of products and goods according to the International Standards Organization (ISO) 14025, 14040, 14044 and EN 15804. EPDs help customers that are environmentally driven to evaluate the performance of a product and to make the best decision when choosing a product. Interface EPDs can be found on interface.com.

Global GreenTag GreenRate - Level A
Global GreenTag's GreenRate certification is a product rating system recognised by the Green Building Council of Australia and Green Building Council of New Zealand. Its assessment scheme aligns to the Green Star® Responsible Products program. All Interface products are certified "Level A".

Best Practice Guidelines for PVC
Our product proudly holds the Best Environmental Practice (BEP) PVC certification, a recognition of compliance with stringent environmental and social criteria in PVC manufacturing. This certification is a key contributor to Green Star certification, aligning with the GBCA's Responsible Products Framework. Our commitment to BEP guidelines demonstrates our dedication to environmental responsibility and product excellence.

Singapore Green Building Product (SGBP)
The SGBP certification is designed to evaluate and certify building products that meet specific sustainability and environmental performance criteria. The certification scheme helps building professionals identify products that are sustainable and more carbon efficient. Interface carpet tile products are certified "Leader" and LVT products are at "Excellent" Level.

NSF Certification
NSF International develops public health standards and certification programs that help protect the world's food, water, consumer products and environment. Interface carpet tile products are certified "Gold".

CRI Green Label Plus
The Carpet and Rug Insitute (CRI) Green Label Plus sets higher standards for indoor air quality and ensures that customers are purchasing the very lowest emitting products on the market. Interface Carpet Tiles and TacTiles have fulfilled the requirements for this certification.

Do more on interface.com

- Browse products, save and share favourites
- See images of products in a variety of room scenes
- Browse floor designs, change colours, upload your own image, download and share
- Get full specifications, sustainability certifications and more
- Sign up to get the latest information on Interface products and news

Our EPDs and certifications contribute credits towards Green Building Council's Green Star® Responsible Products program..

Green Star is the Green Building Council of Australia's sustainability rating system for the built environment. It is used to rate new and existing buildings, new fit-outs, and new precinct developments. The Green Building Council of Australia recognises Responsible Products that may contribute to a Green Star rating through its Responsible Credits.

We have tried our very best to accurately represent product colours. However, due to the nature of printed materials, colour of actual products may vary slightly. Please request a sample to see actual product colour.

Production specifications are subject to normal manufacturing tolerances and may be changed without notice. The visibility of joints may vary based on colour and pattern. Slight variation in colour among different production lots are normal and should be considered in the overall installation plan. Products covered by manufacturer's written warranty only. All other warranties, including without limitation any implied warranties of merchantability or fitness for particular purpose, are hereby disclaimed. Contact your representative for written warranty information.

www.interface.com

Australia
Interface Australia
local toll free: 1800 804 361

India
Interface India
tel: +91 76249 17934

South East Asia
Interface Asia
tel: +65 6478 1510

South Korea
Interface South Korea
tel: +82 2 555 1734

Japan
Interface Japan
tel: +81(0)3-6892-5513

Beijing
Interface China
tel: +86 10 6590 7810

Hong Kong
Interface China
tel: +852 2802 0838

Shanghai
Interface China
tel: +86 21 6340 3868

02/2026