



Printed on 50% post consumer waste (PCW) fiber manufactured using wind power.

interface.com

United States Headquarters

1280 West Peachtree Street NW Atlanta, GA 30309 1.800.634.6032

Canadian Headquarters

233 Lahr Drive Belleville, ON K8N 5S2 1.800.267.2149 ext.52128

Brazilian Headquarters

Av. Das Nações Unidas 14261 25 andar, sala 25 -122, Brooklin Paulista São Paulo 04578 - 000 Brasil + 5511.2196.0900

Latin American Headquarters

Montes Urales # 415 Piso 6 Lomas de Chapultepec Miguel Hidalgo, CDMX 11000 Mexico

+ 52.55.2791.6812

CIM # IFS00913 03/2022



Climate change is undeniable. And reversible. Our mission is to prove it. Join the #ClimateTakeBack and help create a climate fit for life.



Restorative spaces drawn from unexpected places.

Look closely at a desert landscape and you'll find notes of care and comfort—in a warm breeze against the dunes or the soothing earth tones of sand and succulents. Desert Scapes draws inspiration from these restorative moments found in a diverse and demanding environment.

The result is a biophilic healthcare collection – integrating LVT, vinyl sheet and carpet tile – that connects patients and caregivers to the natural world.

Desert Scapes LVT

Desert Scapes offers two 4.5 mm Sound Choice $^{\rm TM}$ LVT styles – both in six colorways, mimicking the desert's tonal transition from day to night.

- Plant-astic[™] A soft crosshatch texture, evoking the look and feel of a weathered burlap etched by desert sands
- Cactus Makes Perfect[™] Unique yet familiar with a soft field of cactus flower layered into the pattern

Like all flooring you specify from Interface, Desert Scapes™ products are carbon neutral across their full product life cycle through our third party verified Carbon Neutral Floors™ program.











Specifications

Product Number Cactus Makes Perfect A021 Plant-astic A022

High Performance Luxury Vinyl Tile Class III Printed Vinyl Plank Product Construction

Class / ASTM F1700

Wear Layer Thickness 22 mil Total Thickness 4.5 mm

Backing Class Commercial Grade

Finish

Ceramor™ Coating 25 cm x 1 m (9.845 in x 39.38 in) Nominal Dimensions

Total Recycled Content (Pre Consumer)

Indoor Air Quality

GREENGUARD Gold FloorScore® Certified

CDPH 01350 Compliant

Carbon Neutral Floors™ Full Life Cycle Carbon Emissions

Environmental Certifications NSF/ANSI 332 Silver

Contributes to multiple IEQ and MR credits LEED v4

View the full product specification on interface.com.

Installation Method





Cactus Makes Perfect



BROWSE IMAGES ORDER SAMPLES Plant-astic



BROWSE IMAGES ORDER SAMPLES

Cactus Makes Perfect™ Colorline



A02101 DESERT SAND



A02103 FOSSIL



A02105 ALOE VERA



A02102 DUNE DUST



A02104 YUCCA



A02106 OASIS

Plant-astic™ Colorline



A02201 DESERT SAND



A02203 FOSSIL



A02205 ALOE VERA



A02202 DUNE DUST



A02204 YUCCA



A02206 OASIS

Integrated System.

Save time and look good doing it. Interface Sound Choice LVT works together with our full product portfolio, including Criterion 3.0 mm LVT, carpet tile, vinyl sheet and nora® rubber. Streamline the specification and installation processes with products that address space-specific performance needs across the entire floorplate of a health system.

Ease of Maintenance.

Create a unique look that lasts. Interface Sound Choice LVT extends the life of your floor. From simple maintenance like damp mopping to selectively replacing damaged tiles, your flooring investment will stand the test of time - beautifully and effortlessly.

Circular System.

Keep flooring out of the landfill. Our modular resilient LVT with Sound Choice™ backing is produced with a controlled material stream so it can be reclaimed and recycled into our CQuest™GB recycled content carpet backing through our ReEntry™ program.

Noise Reduction.

Silence distractions. Interface is helping create +Positive spaces™ with our LVT with Sound Choice backing. Sound Choice is a specially formulated backing developed for superior noise reduction, offering you best-in-class performance for reduced impact sound and floor to floor sound transmission.

We have tried our very best to accurately represent product colors. However, due to the nature of printed materials, color of actual products may vary slightly. Please request a sample to see actual product color.

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see our full LVT product disclaimer at interface.com.

Why Our Modular Resilient Sound Choice[™] 4.5 mm LVT? (continued)



High Performance from Top to Bottom.

- **1.** Ceramor[™] Coating. Minimizes everyday scratching and scuffing.
- **2.** Wear Layer. Transparent, embossed 22 mil wear layer, providing superior resilience and long-lasting performance.
- **3.** *Print Film.* Provides outstanding visuals of natural materials and Interface innovative designs.
- **4.** Core Sheet. Creates a thickness for a stronger core and reduces telegraphing from beneath.
- **5.** Fiberglass. Adds dimensional stability and controlled flexibility.
- **6.** Core Sheet. Creates a thickness for a stronger core and reduces telegraphing from beneath.
- **7.** Sound Choice Backing. Provides comfort and superior acoustic performance.









Third Party Certifications.

Carbon Neutral Floors. Like all the flooring products we sell, Interface Sound Choice LVT is carbon neutral across its full product life cycle through our third party verified Carbon Neutral Floors™ program. To find out more, visit interface. com/carbonneutral.

Environmental Product Declaration (EPD). Interface LVT products are covered by an EPD. An EPD provides a comprehensive statement of product ingredients and environmental impacts based upon life cycle assessment performed to ISO standards.

Sustainable Assessment. Interface LVT meets the certification standards of the NSF/ANSI 332 Sustainability Assessment for Resilient Floor Coverings. This standard evaluates the environmental impact of resilient floor covering for its entire life cycle.

Indoor Air Quality. All Interface modular flooring products meet the highest standards for indoor air quality. Interface LVT is GREENGUARD Gold and FloorScore® Certified and CDPH 01350 compliant, assuring very low emissions of VOCs.