Head Over Heels



Installation Method



Non Directional

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see www.interface.com/disclaimer.

Product Specifications		
Product Number	1267002000	
Product Construction	Tufted Pattern Loop	
Yarn System	100% Recycled Content Nylon	
Yarn Manufacturer	Aquafil	
Dye Method	100% Solution Dyed	
Soil/Stain Protection	Protekt ² ®	
Preservative Protection	Intersept®	
	Imperial	Metric
Tufted Yarn Weight	24 oz/yd²	814 g/m²
Machine Gauge	1/10 in	39.4 ends/10cm
Pile Height	0.17 in	4.3 mm
Pile Thickness	0.098 in	2.5 mm
Stitches	7.5 /in	29.5 ends/10cm
Pile Density	8,816 oz/yd³	326,895 g/m³
Size	39.38 in x 39.38 in	1m x 1m
Performance Specifications		
Flooring Radiant Panel	(ASTM E-648) Passes	
Smoke Density	(ASTM E 662) ≤ 450	
Flammability	Passes Methenamine Pill Test (DOC-FF1-70)	
Lightfastness	(AATCC 16 - E) ≥ 4.0 @ 60 AFU's	
Static	(AATCC - 134) < 3.0 KV	
Dimensional Stability	AACHEN Din 54318 <.10%	
Traffic Classification	Heavy	
Fiber Modification Ratio	1.9 to 2.2	
Preservative Efficacy	(AATCC 174 Parts 2&3) 99% Reduction/No Mold 7 Days (ASTM E-2471) Complete Inhibition	
Health + Environmental Specifica	ations	
Carbon Footprint		
Embodied Carbon (Cradle to Gate)	4.78 (based upon 20 oz face weight) Kg CO_2/M^2 (see in EC3)	
Full Life Cycle Carbon Emissions	Certified Carbon Neutral Floors™	
Total Recycled Content	70%	
Recycled Content (Pre Consumer)	58%	
Recycled Content (Post Consumer)	12%	
Indoor Air Quality	Green Label Plus #GLP0820 CDPH 01350	
Material Composition	Free of Added Heavy Metals, Ortho Phthalates, Formaldehyde, Fluorinated Chemicals (PFAS), and Halogenated Flame Retardants.	