


Head Over Heels

	<																																																																																		
	Product Head Over Heels Color 181729 Head Over Heels Backing GlasBac®																																																																																		
<p>Installation Method</p> <p></p> <p>Non Directional</p> <p>All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see www.interface.com/disclaimer.</p>	<p>Product Specifications</p> <table border="1"> <tr><td>Product Number</td><td colspan="2">1267002500</td></tr> <tr><td>Product Construction</td><td colspan="2">Tufted Pattern Loop</td></tr> <tr><td>Yarn System</td><td colspan="2">100% Recycled Content Nylon</td></tr> <tr><td>Yarn Manufacturer</td><td colspan="2">Aquafil</td></tr> <tr><td>Dye Method</td><td colspan="2">100% Solution Dyed</td></tr> <tr><td>Soil/Stain Protection</td><td colspan="2">Protek®</td></tr> <tr><td>Preservative Protection</td><td colspan="2">Intersept®</td></tr> <tr> <td></td> <td style="text-align: center;">Imperial</td> <td style="text-align: center;">Metric</td> </tr> <tr><td>Tufted Yarn Weight</td><td>24 oz/yd²</td><td>814 g/m²</td></tr> <tr><td>Machine Gauge</td><td>1/10 in</td><td>39.4 ends/10cm</td></tr> <tr><td>Pile Height</td><td>0.17 in</td><td>4.3 mm</td></tr> <tr><td>Pile Thickness</td><td>0.098 in</td><td>2.5 mm</td></tr> <tr><td>Stitches</td><td>7.5 /in</td><td>29.5 ends/10cm</td></tr> <tr><td>Pile Density</td><td>8,816 oz/yd³</td><td>326,895 g/m³</td></tr> <tr><td>Size</td><td>19.69 in x 19.69 in</td><td>50cm x 50cm</td></tr> </table> <p>Performance Specifications</p> <table border="1"> <tr><td>Flooring Radiant Panel</td><td>(ASTM E-648) Passes</td></tr> <tr><td>Smoke Density</td><td>(ASTM E 662) ≤ 450</td></tr> <tr><td>Flammability</td><td>Passes Methenamine Pill Test (DOC-FF1-70)</td></tr> <tr><td>Lightfastness</td><td>(AATCC 16 - E) ≥ 4.0 @ 60 AFU's</td></tr> <tr><td>Static</td><td>(AATCC - 134) < 3.0 KV</td></tr> <tr><td>Dimensional Stability</td><td>AACHEN Din 54318 <.10%</td></tr> <tr><td>Traffic Classification</td><td>Heavy</td></tr> <tr><td>Fiber Modification Ratio</td><td>1.9 to 2.2</td></tr> <tr><td>Preservative Efficacy</td><td>(AATCC 174 Parts 2&3) 99% Reduction/No Mold 7 Days (ASTM E-2471) Complete Inhibition</td></tr> </table> <p>Health + Environmental Specifications</p> <table border="1"> <tr><td colspan="2">Carbon Footprint</td></tr> <tr><td>Embodied Carbon (Cradle to Gate)</td><td>4.78 (based upon 20 oz face weight) Kg CO₂/M² (see in EC3)</td></tr> <tr><td>Full Life Cycle Carbon Emissions</td><td>Certified Carbon Neutral Floors™</td></tr> <tr><td>Total Recycled Content</td><td>70%</td></tr> <tr><td>Recycled Content (Pre Consumer)</td><td>58%</td></tr> <tr><td>Recycled Content (Post Consumer)</td><td>12%</td></tr> <tr><td>Indoor Air Quality</td><td>Green Label Plus #GLP0820 CDPH 01350</td></tr> <tr><td>Material Composition</td><td>Free of Added Heavy Metals, Ortho Phthalates, Formaldehyde, Fluorinated Chemicals (PFAS), and Halogenated Flame Retardants.</td></tr> <tr><td colspan="2">Disclosure of Environmental Impacts</td></tr> </table>		Product Number	1267002500		Product Construction	Tufted Pattern Loop		Yarn System	100% Recycled Content Nylon		Yarn Manufacturer	Aquafil		Dye Method	100% Solution Dyed		Soil/Stain Protection	Protek®		Preservative Protection	Intersept®			Imperial	Metric	Tufted Yarn Weight	24 oz/yd ²	814 g/m ²	Machine Gauge	1/10 in	39.4 ends/10cm	Pile Height	0.17 in	4.3 mm	Pile Thickness	0.098 in	2.5 mm	Stitches	7.5 /in	29.5 ends/10cm	Pile Density	8,816 oz/yd ³	326,895 g/m ³	Size	19.69 in x 19.69 in	50cm x 50cm	Flooring Radiant Panel	(ASTM E-648) Passes	Smoke Density	(ASTM E 662) ≤ 450	Flammability	Passes Methenamine Pill Test (DOC-FF1-70)	Lightfastness	(AATCC 16 - E) ≥ 4.0 @ 60 AFU's	Static	(AATCC - 134) < 3.0 KV	Dimensional Stability	AACHEN Din 54318 <.10%	Traffic Classification	Heavy	Fiber Modification Ratio	1.9 to 2.2	Preservative Efficacy	(AATCC 174 Parts 2&3) 99% Reduction/No Mold 7 Days (ASTM E-2471) Complete Inhibition	Carbon Footprint		Embodied Carbon (Cradle to Gate)	4.78 (based upon 20 oz face weight) Kg CO ₂ /M ² (see in EC3)	Full Life Cycle Carbon Emissions	Certified Carbon Neutral Floors™	Total Recycled Content	70%	Recycled Content (Pre Consumer)	58%	Recycled Content (Post Consumer)	12%	Indoor Air Quality	Green Label Plus #GLP0820 CDPH 01350	Material Composition	Free of Added Heavy Metals, Ortho Phthalates, Formaldehyde, Fluorinated Chemicals (PFAS), and Halogenated Flame Retardants.	Disclosure of Environmental Impacts	
Product Number	1267002500																																																																																		
Product Construction	Tufted Pattern Loop																																																																																		
Yarn System	100% Recycled Content Nylon																																																																																		
Yarn Manufacturer	Aquafil																																																																																		
Dye Method	100% Solution Dyed																																																																																		
Soil/Stain Protection	Protek®																																																																																		
Preservative Protection	Intersept®																																																																																		
	Imperial	Metric																																																																																	
Tufted Yarn Weight	24 oz/yd ²	814 g/m ²																																																																																	
Machine Gauge	1/10 in	39.4 ends/10cm																																																																																	
Pile Height	0.17 in	4.3 mm																																																																																	
Pile Thickness	0.098 in	2.5 mm																																																																																	
Stitches	7.5 /in	29.5 ends/10cm																																																																																	
Pile Density	8,816 oz/yd ³	326,895 g/m ³																																																																																	
Size	19.69 in x 19.69 in	50cm x 50cm																																																																																	
Flooring Radiant Panel	(ASTM E-648) Passes																																																																																		
Smoke Density	(ASTM E 662) ≤ 450																																																																																		
Flammability	Passes Methenamine Pill Test (DOC-FF1-70)																																																																																		
Lightfastness	(AATCC 16 - E) ≥ 4.0 @ 60 AFU's																																																																																		
Static	(AATCC - 134) < 3.0 KV																																																																																		
Dimensional Stability	AACHEN Din 54318 <.10%																																																																																		
Traffic Classification	Heavy																																																																																		
Fiber Modification Ratio	1.9 to 2.2																																																																																		
Preservative Efficacy	(AATCC 174 Parts 2&3) 99% Reduction/No Mold 7 Days (ASTM E-2471) Complete Inhibition																																																																																		
Carbon Footprint																																																																																			
Embodied Carbon (Cradle to Gate)	4.78 (based upon 20 oz face weight) Kg CO ₂ /M ² (see in EC3)																																																																																		
Full Life Cycle Carbon Emissions	Certified Carbon Neutral Floors™																																																																																		
Total Recycled Content	70%																																																																																		
Recycled Content (Pre Consumer)	58%																																																																																		
Recycled Content (Post Consumer)	12%																																																																																		
Indoor Air Quality	Green Label Plus #GLP0820 CDPH 01350																																																																																		
Material Composition	Free of Added Heavy Metals, Ortho Phthalates, Formaldehyde, Fluorinated Chemicals (PFAS), and Halogenated Flame Retardants.																																																																																		
Disclosure of Environmental Impacts																																																																																			