

Steady Stride Woodgrains | LV1



Interface®

A shrewd balance of design and performance, Steady Stride™ Woodgrains is something that you'll come back to again and again. It introduces a slimmer dimension on the floor with its 12.5 cm x 1 m planks.

Steady Stride Woodgrains is 3.0 mm thick, including a 22 mil wear layer with Ceramor™ coating, and is backed by a 15-year warranty.

And at Interface, we're 'all in' on becoming a restorative business, driving toward positive impacts. As part of our commitment, Steady Stride Woodgrains contains 39% recycled content.







interface.com

PRODUCT STEADY STRIDE WOODGRAINS COLOR GRAPHITE INSTALLED ASHLAR



PRODUCT STEADY STRIDE WOODGRAINS COLOR STERLING INSTALLED ASHLAR

Specifications

Product Number	B001
3.0 mm	
Product Construction	High Performance Luxury Vinyl Tile
Class/ASTM F1700	Class III Printed Vinyl Tile
Wear Layer Thickness	22 mil
Total Thickness	3.0 mm
Backing Class	Commercial Grade
Finish	Ceramor™ Coating
Nominal Dimensions	12.5 cm x 1 m (4.923 in x 39.38 in)
Total Recycled Content (Pre Consumer)	39%
Indoor Air Quality	GREENGUARD Gold FloorScore® Certified
Environmental Certifications	CDPH 01350 Compliant
LEED v4	NSF/ANSI 332 Silver Contributes to multiple IEQ and MR credits

View the full product specification on [interface.com](#)

Installation Methods



ASHLAR



HERRINGBONE

Ready for More?

Find the latest color options, formats and full specifications on [Interface.com](#). Create an account or login to take the next step for your project.

3.0 mm LVT



CHECK AVAILABILITY
ORDER SAMPLES

Steady Stride™ Woodgrains Color Range



3.0 mm B00101 BISCUIT



3.0 mm B00102 BRISTLE



3.0 mm B00103 MALT



3.0 mm B00104 DRIFTWOOD



3.0 mm B00105 NICKEL



3.0 mm B00106 BLONDE



3.0 mm B00107 BARLEY



3.0 mm B00109 ELM



3.0 mm B00110 MOCHA



3.0 mm B00113 GRAPHITE



3.0 mm B00114 STERLING

Why Our Modular Resilient 3.0 mm LVT?



Integrated System
Save time and look good doing it. Our 3.0 mm LVT integrates with our full product portfolio, allowing you to streamline specification and installation of your floorplate. Add our modular carpet for an inset rug or an adjacent field – Most carpet products on GlasBac™ or CQuest™GB backing that are 17 oz or less are approved to be used next to 3.0 mm LVT without a transition strip.



Easy Maintenance
Create a unique look that lasts. Interface LVT extends the life of your floor. From the hardwearing Ceramor™ coating that resists scratches and scuffs to simple damp mopping, your flooring investment will stand the test of time - beautifully and effortlessly.



Sustainable Choice
Interface is committed to offering flooring that helps you lower your environmental impact. Our 3.0 mm LVT contains 39% recycled content.

High Performance from Top to Bottom



- 1. Ceramor™ Coating.** Minimizes everyday scratching and scuffing.
- 2. Wear Layer.** High quality 22 mil layer enabling 15 years of resilience and performance.
- 3. Print Film.** Provides outstanding visuals of natural materials and Interface innovative designs.
- 4. Core Sheet.** Creates a thickness for a stronger core and reduces telegraphing from beneath.
- 5. Backing.** Provides resistance to residual indentation.

Our 3.0 mm LVT is engineered to create a smooth transition to nora® rubber flooring - no transition strips required.



Environmental Product Declaration (EPD)
A third party verified statement of product ingredients and environmental impacts over the entire life cycle of a product.



GREENGUARD Gold & FloorScore®
Meeting the highest standards for indoor air quality and assuring very low emissions of VOCs, Interface LVT is GREENGUARD Gold and FloorScore® Certified and CDPH 01350 compliant.



Health Product Declaration (HPD)
A transparency tool for evaluating if a product includes materials of concern and whether it supports Green Chemistry.



NSF/ANSI 332 Silver
This standard evaluates the environmental impact of resilient floor covering for its entire life cycle.

📍 Samples
Register and order samples at [interface.com](https://www.interface.com). Not near a computer? You can also request samples by calling one of the numbers below.

United States
1.877.605.1500

Canada
1.866.398.3192

- interface.com**
Do more on [interface.com](https://www.interface.com)
- Browse products and order samples
 - Save and share favorites
 - See images of products in a variety of room scenes
 - Browse floor designs, change colors, upload your own image, download and share
 - Get full specifications, sustainability certifications and more
 - Check order status and inventory availability
 - Sign up to get the latest information on Interface products and news

We have tried our very best to accurately represent product colors. However, due to the nature of printed materials, color of actual products may vary slightly. Please request a sample to see actual product color.

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see [interface.com/disclaimer](https://www.interface.com/disclaimer).



PLEASE RECYCLE

Printed on 50% post consumer waste (PCW)
fiber manufactured using wind power.

interface.com

United States Headquarters

1280 West Peachtree Street NW
Atlanta, GA 30309
1.800.634.6032

Canadian Headquarters

233 Lahr Drive
Belleville, ON K8N 5S2
1.800.267.2149 ext. 52128

CIM# IFS00945 06/2024



Climate change is undeniable. And
reversible. Our mission is to prove it.
**Join the #ClimateTakeBack and
help create a climate fit for life.**