



Step Repeat Collection

SR699
SR799
SR899
SR999

Interface®

Step Repeat™ Collection

The Step Repeat Collection offers four coordinating styles designed to make the most of your entryways and other high traffic areas. From the simple lines of SR699 to the larger scale pattern of SR999, each style features innovative, stiff fibers that grab dirt, moisture and debris, trapping it until it can be vacuumed up later. So interiors stay fresher and your carpet lasts longer. Step Repeat is available in eight earthy, neutrals.





Step Repeat™ vs Typical Entry Carpet Tile

	Interface's Step Repeat	Typical Entry Carpet Tile
Installation Method	Non Directional Option with SR999	Monolithic or Quarter-Turn only
Radiant Panel (Class 1)	Passes	Fails
Soil Retention	4 lbs	1.8 lbs
Yarn System	Nylon	Polypropylene
Preservative Protection	Intersept®	None
Soil/Stain Protection	Protekt ² ™	None
Classification	Severe	Moderate
Warranty	15 years	1-3 years



SR699 Color Range



104930 SMOKE



104931 GRANITE



104932 IRON



104933 ONYX



104911 KHAKI



104912 SABLE



104913 DARK BROWN



104914 MIDNIGHT

Specifications

Modular, 50 cm x 50 cm	13884
Yarn Manufacturer	Aquafil
Yarn System	100% Recycled Content Nylon
Dye Method	100% Solution Dyed
Construction	Tufted Textured Loop
Preservative Protection	Intersept®
Soil/Stain Protection	Protekt ² ™
Pile Thickness	0.15 in, 3.7 mm
Pile Density	6,612 oz/yd ³
Total Recycled Content	66%
Indoor Air Quality	CRI Green Label Plus #GLP0820

View the full product specification on [interface.com](#)

Installation Method



QUARTER-TURN



BROWSE IMAGES
ORDER SAMPLES

SR799 Color Range



104934 SMOKE



104935 GRANITE



104936 IRON



104937 ONYX




104915 KHAKI



104916 SABLE



104917 DARK BROWN



104918 MIDNIGHT

Specifications

Modular, 50 cm x 50 cm	13885
Yarn Manufacturer	Aquafil
Yarn System	100% Recycled Content Nylon
Dye Method	100% Solution Dyed
Construction	Tufted Textured Loop
Preservative Protection	Intersept®
Soil/Stain Protection	Protek12™
Pile Thickness	0.14 in, 3.6 mm
Pile Density	6,686 oz/yd³
Total Recycled Content	66%
Indoor Air Quality	CRI Green Label Plus #GLP0820

View the full product specification on [interface.com](#)

Installation Method



QUARTER-TURN



BROWSE IMAGES
ORDER SAMPLES

PRODUCT SR799 COLOR GRANITE INSTALLED QUARTER-TURN





SR899 Color Range



104938 SMOKE



104939 GRANITE



104940 IRON



104941 ONYX



104919 KHAKI



104920 SABLE



104921 DARK BROWN



104922 MIDNIGHT

Specifications

Modular, 50 cm x 50 cm	13886
Yarn Manufacturer	Aquafil
Yarn System	100% Recycled Content Nylon
Dye Method	100% Solution Dyed
Construction	Tufted Textured Loop
Preservative Protection	Intersept®
Soil/Stain Protection	Protekt ² ™
Pile Thickness	0.14 in, 3.6 mm
Pile Density	6,545 oz/yd³
Total Recycled Content	66%
Indoor Air Quality	CRI Green Label Plus #GLP0820

View the full product specification on [interface.com](https://www.interface.com)

Installation Method



BROWSE IMAGES
ORDER SAMPLES

SR999 Color Range



104942 SMOKE



104943 GRANITE



104944 IRON



104945 ONYX



104923 KHAKI



104924 SABLE



104925 DARK BROWN



104926 MIDNIGHT

Specifications

Modular, 50 cm x 50 cm	13887
Yarn Manufacturer	Aquafil
Yarn System	100% Recycled Content Nylon
Dye Method	100% Solution Dyed
Construction	Tufted Textured Loop
Preservative Protection	Intersept®
Soil/Stain Protection	Protek12™
Pile Thickness	0.13 in, 3.2 mm
Pile Density	7,654 oz/yd³
Total Recycled Content	66%
Indoor Air Quality	CRI Green Label Plus #GLP0820

View the full product specification on [interface.com](#)

Installation Method



NONDIRECTIONAL



BROWSE IMAGES
ORDER SAMPLES




PRODUCT SR999 COLOR SMOKE INSTALLED NON DIRECTIONAL


Why Our Modular Flooring?



Modular Flooring
Performance and flexibility. Interface's standard backing systems set the industry standard for modular performance. Tiles stay on the floor with no upcurl, no taping and no rippling effect, yet are easy to selectively replace. Our modular carpet is easier to handle than bulky roll carpet and produces an average of just 3-4% waste compared to roll carpet's average of 14%. And it installs seamlessly with our LVT, no transition strips needed.



TacTiles™
No glue installation. Our revolutionary TacTiles installation system eliminates the need for glue, adhering tiles securely together to form a floor that “floats” for greater flexibility, easier replacement and long-term performance. The result? Less mess, less waste and virtually no VOCs, not to mention an environmental footprint that is over 90% lower than that of traditional glue adhesives. TacTiles are approved for use on GlasBac™, CQuest™GB, CQuest™Bio and CQuest™BioX.




Intersept®
Mold protection. Our proprietary preservative, Intersept, protects our modular carpet against mold growth and odor-causing bacteria—guaranteed. Intersept treated carpet, with proper maintenance, shows no mold or bacterial growth when tested per the ASTM E2471 Standard Test Method. Intersept is EPA approved for safe use in carpet, water insoluble and contains no halogens, heavy metals, phenols or formaldehyde. Intersept is standard in Interface carpet tile products backed with GlasBac, CQuestGB, ReadyBac™ and CushionBac Renew™.



Environmental Product Declaration (EPD)
A statement of product ingredients and environmental impacts over the entire life cycle of a product. A comprehensive life cycle assessment (LCA) is performed to ISO standards to develop an EPD, after which both the EPD and LCA must be third party verified.



Health Product Declaration (HPD)
A transparency tool for evaluating whether a product supports Green Chemistry. As part of our work on Health and Materials, Interface continuously reduces the environmental and health impacts of our products through elimination of materials of concern.



ReEntry™
Recyclable. Through our ReEntry program we reclaim and recycle our carpet tile and Sound Choice™ LVT. ReEntry is the only third party certified recycling system among North American flooring manufacturers.



Sustainability Transparency
Transparency and certified sustainability leadership come standard on Interface products. We enlist outside partners to help us evaluate the entire product life cycle and reduce the environmental and human health impact of our flooring. And, carpet products made in our US facilities are made with 99% renewable energy.



CRI Green Label Plus
An independent testing program that identifies carpet and adhesives with very low emissions of VOCs to help improve indoor air quality.



NSF 140 Sustainable Carpet Assessment
The only carpet sustainability standard in North America that evaluates the environmental impact of carpet for its entire life cycle.

📍 **Samples**

Register and order samples at interface.com. Not near a computer? You can also request samples by calling one of the numbers below.

United States
1.877.605.1500

Canada
1.866.398.3192

interface.com

- Do more on interface.com
- Browse products and order samples
 - Save and share favorites
 - See images of products in a variety of room scenes
 - Browse floor designs, change colors, upload your own image, download and share
 - Get full specifications, sustainability certifications and more
 - Check order status and inventory availability
 - Sign up to get the latest information on Interface products and news

InterCircle Sample Return

Help us close the loop on the carpet sampling process. Through our InterCircle Sample Return program, sample materials stay out of the landfill and are re-used as samples until it is time to recycle them into new carpet. By reducing sample production material and diverting old materials from the landfill, we can reduce our overall environmental footprint.

Call 1.877.605.1500 (U.S.) or 1.866.398.3192 (Canada) to order a sample return bag with a prepaid return label.

We have tried our very best to accurately represent product colors. However, due to the nature of printed materials, color of actual products may vary slightly. Please request a sample to see actual product color.

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see interface.com/disclaimer.



Printed on 50% post consumer waste (PCW)
fiber manufactured using wind power.

interface.com

United States Headquarters

1280 West Peachtree Street NW
Atlanta, GA 30309
1.800.634.6032

Canadian Headquarters

233 Lahr Drive
Belleville, ON K8N 5S2
1.800.267.2149 ext. 52128

CIM# IFS00696 01/2025