



Installation Method



Ashlar

Herringbone

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see www.interface.com/disclaimer.

Product NF401 **Color** Shale **Collection** Near & Far Collection **Backing** GlasBac™

Product Specifications

| | |
|-------------------------|-----------------------------|
| Product Number | 127860AK00 |
| Product Construction | Engaged Tufted Sheared |
| Yarn System | 100% Recycled Content Nylon |
| Yarn Manufacturer | Aquafil |
| Dye Method | 100% Solution Dyed |
| Soil/Stain Protection | Protekt ² ® |
| Preservative Protection | Intersept® |

More Product Specifications

| | Imperial | Metric |
|--------------------|--------------------------|--------------------------|
| Tufted Yarn Weight | 34 oz/yd ² | 1,153 g/m ² |
| Machine Gauge | 1/10 in | 39.4 ends/10cm |
| Pile Height | 0.22 in | 5.60 mm |
| Pile Thickness | 0.17 in | 4.40 mm |
| Stitches | 7.50 /in | 29.53 ends/10cm |
| Pile Density | 7,075 oz/yd ³ | 262,339 g/m ³ |
| Size | 9.845 in x 39.38 in | 25cm x 1m |

Performance Specifications

| | |
|--------------------------|--|
| Flooring Radiant Panel | (ASTM E-648) Passes |
| Smoke Density | (ASTM E-662) ≤ 450 |
| Flammability | Passes Methenamine Pill Test (DOC-FF1-70) |
| Lightfastness | (AATCC 16 - E) ≥ 4.0 @ 60 AFU's |
| Static | (AATCC - 134) < 3.0 KV |
| Dimensional Stability | AACHEN Din 54318 < 0.10% |
| Traffic Classification | Moderate |
| Fiber Modification Ratio | 1.9 to 2.2 |
| Preservative Efficacy | (AATCC 174 Parts 2&3) 99% Reduction/No Mold 7 Days (ASTM E-2471) Complete Inhibition |

Health + Environmental Specifications

| | |
|-------------------------------------|---|
| Embodied Carbon (Cradle to Gate) | 5.88 Kg CO ₂ /M ² |
| Total Recycled Content | 72.54 % |
| Recycled Content (Pre Consumer) | 56.90 % |
| Recycled Content (Post Consumer) | 15.64 % |
| Indoor Air Quality | Green Label Plus #GLP0820 |
| Material Composition | Free of Added Heavy Metals, Formaldehyde, Fluorinated Chemicals (PFAS), and Halogenated Flame Retardants. |
| Disclosure of Environmental Impacts | Environmental Product Declaration |
| Disclosure of Product Ingredients | Health Product Declaration |
| Environmental Certifications | NSF/ANSI 140 Gold |
| LEED v4 | Contributes to multiple IEQ and MR credits |
| End of Life | Carpet to Carpet Recycling through ReEntry® |

Technical Information

| | |
|------------------------|--|
| Installation | Interface Installation Guidelines |
| Maintenance | Recommended Interface Maintenance Guidelines |
| Reclamation | Recyclable through ReEntry® - Call 1.888.733.6873 (U.S.) / 1.866.398.3191 (Canada) |
| Warranty | 15 Year Standard Carpet Warranty |
| Installation Method | Ashlar Herringbone |
| Manufacturing Location | ISO 9001 & 14001 Certified facilities in Troup County, Georgia, United States |