



**Installation Method**



Ashlar

Brick

Non Directional



Quarter turn

Monolithic

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see [www.interface.com/disclaimer](http://www.interface.com/disclaimer).

**Product** Raku **Color** Morning Mist **Collection** Global Change Collection **Backing** GlasBac™

**Product Specifications**

Product Number	1426802500
Product Construction	Engaged Tufted Sheared
Yarn System	Post-Consumer Content Nylon
Yarn Manufacturer	Universal
Dye Method	100% Solution Dyed
Soil/Stain Protection	Protekt <sup>2</sup> ®
Preservative Protection	Intersept®

**More Product Specifications**

	Imperial	Metric
Tufted Yarn Weight	30 oz/yd <sup>2</sup>	1,017 g/m <sup>2</sup>
Machine Gauge	1/10 in	39.4 ends/10cm
Pile Height	0.18 in	4.60 mm
Pile Thickness	0.13 in	3.30 mm
Stitches	10.00 /in	39.37 ends/10cm
Pile Density	8,438 oz/yd <sup>3</sup>	312,879 g/m <sup>3</sup>
Size	19.69 in x 19.69 in	50cm x 50cm

**Performance Specifications**

Flooring Radiant Panel	(ASTM E-648) Passes
Smoke Density	(ASTM E-662) ≤ 450
Flammability	Passes Methenamine Pill Test (DOC-FF1-70)
Lightfastness	(AATCC 16 - E) ≥ 4.0 @ 60 AFU's
Static	(AATCC - 134) < 3.0 KV
Dimensional Stability	AACHEN Din 54318 < 0.10%
Traffic Classification	Heavy
Fiber Modification Ratio	1.7 to 1.9
Preservative Efficacy	(AATCC 174 Parts 2&3) 99% Reduction/No Mold 7 Days (ASTM E-2471) Complete Inhibition

**Health + Environmental Specifications**

Embodied Carbon (Cradle to Gate)	5.56 Kg CO <sub>2</sub> /M <sup>2</sup>
Total Recycled Content	65.44 %
Recycled Content (Pre Consumer)	63.71 %
Recycled Content (Post Consumer)	1.73 %
Indoor Air Quality	<a href="#">Green Label Plus #GLP0820</a>
Material Composition	Free of Added Heavy Metals, Formaldehyde, Fluorinated Chemicals (PFAS), and Halogenated Flame Retardants.
Disclosure of Environmental Impacts	<a href="#">Environmental Product Declaration</a>
Disclosure of Product Ingredients	<a href="#">Health Product Declaration</a>
Environmental Certifications	<a href="#">NSF/ANSI 140 Gold</a>
LEED v4	Contributes to multiple IEQ and MR credits
End of Life	Carpet to Carpet Recycling through ReEntry®

**Technical Information**

Installation	<a href="#">Interface Installation Guidelines</a>
Maintenance	<a href="#">Recommended Interface Maintenance Guidelines</a>
Reclamation	Recyclable through ReEntry® - Call 1.888.733.6873 (U.S.) / 1.866.398.3191 (Canada)
Warranty	<a href="#">15 Year Standard Carpet Warranty</a>
Installation Method	Monolithic Quarter Turn Non Directional Ashlar Brick
Manufacturing Location	ISO 9001 & 14001 Certified facilities in Troup County, Georgia, United States