


Installation Method



Monolithic

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see www.interface.com/disclaimer.

Product Twist & Shine Micro **Color** Midnight Micro **Backing** CQuest™Bio

Product Specifications

Product Number	107800250B
Product Construction	Tufted Level Loop
Yarn System	100% Recycled Content Nylon
Yarn Manufacturer	Aquafil
Dye Method	100% Solution Dyed
Soil/Stain Protection	Protect ² ®

More Product Specifications

	Imperial	Metric
Tufted Yarn Weight	16 oz/yd ²	509 g/m ²
Machine Gauge	5/64 in	50.4 ends/10cm
Pile Height	0.06 in	1.50 mm
Pile Thickness	0.02 in	0.50 mm
Stitches		0.00 ends/10cm
Pile Density	30,316 oz/yd ³	1,124,111 g/m ³
Size	19.69 in x 19.69 in	50cm x 50cm

Performance Specifications

Flooring Radiant Panel	(ASTM E-648) Passes
Smoke Density	(ASTM E-662) ≤ 450
Flammability	Passes Methenamine Pill Test (DOC-FF1-70)
Lightfastness	(AATCC 16 - E) ≥ 4.0 @ 60 AFU's
Static	(AATCC - 134) < 3.0 KV
Dimensional Stability	AACHEN Din 54318 < 0.10%
Traffic Classification	Severe
Fiber Modification Ratio	1.9 to 2.2

Health + Environmental Specifications

Embodied Carbon (Cradle to Gate)	2.48 Kg CO ₂ /M ²
Biobased Content	Interface Modular Carpet on CQuestBio contains 47% USDA certified biobased content
Total Recycled Content	60.84 %
Recycled Content (Pre Consumer)	60.58 %
Recycled Content (Post Consumer)	0.26 %
Indoor Air Quality	K1
Material Composition	Free of Added Heavy Metals, Formaldehyde, Fluorinated Chemicals (PFAS), and Halogenated Flame Retardants.
Disclosure of Environmental Impacts	Environmental Product Declaration
Disclosure of Product Ingredients	Health Product Declaration
Environmental Certifications	K1
LEED v4	K1
End of Life	Reclaimed through ReEntry®

Technical Information

Installation	Interface Installation Guidelines
Maintenance	Recommended Interface Maintenance Guidelines
Reclamation	Reclaimed through ReEntry®
Warranty	15 Year Standard Carpet Warranty
Installation Method	Monolithic
Manufacturing Location	ISO 9001 & 14001 Certified facilities in Troup County, Georgia, United States