

SYDNEY CARPET LABORATORY

OF INTERFACE AUST, PTY LIMITED - ABN 39 000 692 026

34 AIRDS ROAD, MINTO NSW 2566 - TEL: (02) 8706 4632

TEST REPORT

Client: Interface Australia PTY LTD

34 Airds Road Minto

NSW 2566 Australia Test Report No: Sample Received Date: R21-160 31/05/2021

Test Date: 29/07/2021 Report Date: 29/07/2021

Sample Description: Client Reference: "OPEN AIR 405"

100% Solution Dyed Nylon 6 610g/m² on a Glasbac Backing

AS ISO 9239.1-2003: Reaction to Fire Tests for Floorings – Determination of the Burning Behaviour Using a Radiant Heat Source

Results Summary

CHF Value	Sample 1	Sample 2	Sample 3	Mean	
Length	3.7	3.3	3.5	3.5	kW/m²
Width	3.7	-	-	-	kW/m²
Smoke Value	Sample 1	Sample 2	Sample 3	Mean	
Length	164	157	170	164	%.min
Width	178	-	-	-	%.min
Melting		YES			
Blistering			YES		

The test results relate to the behaviour of the test specimens of a product under the particular conditions of the test, they are not intended to be sole criterion for assessing the potential fire hazard of the product in use.

Sample was conditioned in accordance with BS EN 13238 at a temperature of 23±2°C and relative humidity of 50±5% for a minimum of 48 hours prior to testing.

Each Specimen was adhered to a substrate of 9mm Fibre Cement Board using Intertac+ Adhesive.

END OF REPORT

Page 1 of 1

Accreditation No.2834.

Accredited for compliance with ISO/IEC 17025 - Testing

The results of the test, calibrations and/or measurements included in this document are traceable to Australian/ International Standards.

This report may not be reproduced except in full and shall be rendered void if amended or altered.

This document may not be used in any form without prior consent.

The results on this report are related only to the items tested.