

SYDNEY CARPET LAB

34 AIRDS ROAD, MINTO NSW 2566 - TEL: (02) 8706 4600 FAX: (02) 8706 4617

TEST REPORT

Client: Interface Australia PTY LTD

34 Airds Road Minto NSW 2566 Test Report No: D11-19-005

Sample Received date: 07/01/2019

Test Date: 15/01/2019 Report Date: 18/01/2019

Client Reference: "OVEREDGE" Sample Description:

> 100% Solution Dyed Nylon 6 1424g/m2 on a Glasbac Backing

AS ISO 9239.1: Reaction to Fire Tests for Floorings – Determination of the Burning Behaviour Using a Radiant Heat Source

Results Summary

CHF Value	Sample 1	Sample 2	Sample 3	Mean	
Length	5.1	5.5	5.3	5.3	kW/m²
Width	5.1	-	-	-	kW/m²
Smoke Value	Sample 1	Sample 2	Sample 3	Mean	
Length	187	199	170	186	%.min
Width	206	-	-	-	%.min
Melting			Yes		
Blistering			Yes		

The test results relate to the behaviour of the test specimens of a product under the particular conditions of the test, they are not intended to be sole criterion for assessing the potential fire hazard of the product in use.

Sample was conditioned in accordance with BS EN 13238 at a temperature of 23±2°C and relative humidity of 50±5% for a minimum of 48 hours prior to testing.

Each Specimen was adhered to a substrate of 9mm thick fibre cement board using Intertac adhesive.

END OF REPORT

Page 1 of 1

Accreditation No.2834.

Accredited for compliance with ISO/IEC 17025 - Testing

The results of the test, calibrations and/or measurements included in this document are traceable to Australian/ International Standards.

This report may not be reproduced except in full and shall be rendered void if amended or altered.

MICHAEL BOYD